

aluplast GmbH (Head Office)
Kunststoff-Fenstersysteme
Auf der Breit 2
DE - 76227 Karlsruhe

fon: +49 721 47171-0
fax: +49 721 47171-999
info.de@aluplast.net
www.aluplast.net

Plans of Profiles
Export / Tropical
(INDIA)

Germany
KARLSRUHE (HQ)
ETTLINGEN

PENNSYLVANIA, USA

TEXAS, USA

MEXICO

RUSSIA

UKRAINE

POLAND

AUSTRIA

INDIA

Good together. Strong together.

At home all over the world

Albania
Algeria
Argentina
Armenia
Australia
Belarus
Belgium
Bhutan
Bosnia - Herzegovina
Brazil

Bulgaria
Cambodia
Cameroon
Canada
Chile
China
Colombia
Costa Rica
Croatia
Cyprus

Czech Republic
Denmark
Ecuador
Egypt
France
Georgia
Germany
Greece
Great Britain
Guatemala

Honduras
Hungary
Indonesia
Iraq
Ireland
Italy
Kazakhstan
Kyrgyzstan
Korea
Kosovo

Latvia
Lebanon
Lithuania
Malaysia
Malta
Morocco
Macedonia
Moldova
Mongolia
Montenegro

New Zealand
Nicaragua
Netherlands
Nigeria
Oman
Paraguay
Philippines
Qatar
Romania
Saudi Arabia

Sweden
Switzerland
Serbia
Slovakia
Slovenia
Spain
Sri Lanka
South Africa
Thailand
Tunisia

Turkey
United Arab Emirates
Uruguay
Uzbekistan
Vietnam



2 revolving seal levels
external and internal

modern design: chamfers and
round edges internal and
external


frames, sashes, mullions with
multi chambers for good
heat insulation

glazing-strength up to 33mm



13mm dimension
between axes for better
prevention of burglary



IDEAL 2000



Balcony door
IDEAL 2000



IDEAL 4000
5 chamber system / 70mm

2 revolving seal levels
external and internal

big reinforcement
chamber for
high static values

modern design: chamfers and
round edges internal and
external



frames, sashes, mullions with multi
chambers for good heat insulation

glazing-strength up to 42mm

13mm dimension
between axes for better
prevention of burglary

good sealing by
high overlap

possibility of disguised
drainage



Front door
IDEAL 4000


2 revolving seal levels
external and internal

modern design: chamfers and round
edges internal and external


frames, sashes, mullions with multi
chambers for good heat insulation

glazing-strength up to
42mm


22.5mm dimension
between axes



CASEMENT 4000
5 chamber system / 70mm



mono-slide window





big reinforcement chamber
for high static value

glazing strength up to 25 mm

optional bonding inside
(adhesive technology)

screw channels for frame
corner connection

3-track 126 mm frame




Vario-Slide

big reinforcement
chamber for high static value


glazing strength up to 33 mm

easy to connect for 3, 4 or more
sashes, wide opening possible

frames, sashes, mullions with multi
chambers for good heat insulation



Multi-Slide



Smart-Slide

modern design: chamfers and round
edges internal and external


frames, sashes, mullions with multi
chambers for good heat insulation

glazing-strength up to
51mm

screw ducts for better edge stability of
the architecture junction

2 revolving seal levels
external and internal




big reinforcement for
high static value







Lift-Slide

IDEAL 2000 Classic-line (CL)



Frame





Sash



Mullion



False mullion



Ⓜ Bonding of pane Option

☐ not laminated
■ laminated


IA| Spacer
IC| End caps
ID| Connector
ID| Connector without sticks
IF| Reinforcements
IJ| Bonding of pane
IP| **aluskin** Aluminium shells
IQ| Aluminium step protection
IU| Aluminium threshold
IV| Threshold connector
M Mullion coupler
X| Gaskets

-> for
TBA in preparation
(new or modified)















(CL) Classic-line
(RL) Round-line
(SL) Soft-line

(MB) Monobloc


IDEAL 4000®
Classic-line (CL)



Aluminium shells



Gaskets



Gaskets



④ Bonding of pane

☒ not laminated

- ☐ A| Spacer
- ☐ C| End caps
- ☐ D| Connector
- ☒ E| Connector without sticks

-> for

(73)





$$\begin{pmatrix} SL \\ RL \end{pmatrix}$$

(MB)











TBA

n (Engl)










Extensions







Couplings - Structural profiles



General




Accessories




□ not laminated
■ foam inside -> □
-> for

gm green
pw papyrus-white
white




Construction depth
->IDEAL 2000
->60mm
->IDEAL 4000 / 5000
->60mm
->IDEAL 7000 / 8000
->85mm
...
SL viable length
AU exterior perimeter
GU overall perimeter



Main Profiles



Accessories





a e.g. Profile serial		C-3)	d	Glazing thickness															
85mm	IDEAL 7000 + 16mm + 4mm protrusion	-	→170x39	40 - 41mm	42 - 43mm	44 - 45mm	46 - 47mm	48 - 49mm	50 - 51mm	52 - 53mm	54 - 55mm	56 - 57mm	58 - 59mm	60 - 61mm	62 - 63mm	64 - 65mm	66 - 67mm	68 - 69mm	70 - 71mm
81mm	IDEAL 7000 + 16mm + 0mm protrusion	-	→170x39	36 - 37mm	38 - 39mm	40 - 41mm	42 - 43mm	44 - 45mm	46 - 47mm	48 - 49mm	50 - 51mm	52 - 53mm	54 - 55mm	56 - 57mm	58 - 59mm	60 - 61mm	62 - 63mm	64 - 65mm	66 - 67mm
73mm	IDEAL 8000 + 8mm / 180250 → 180x69	→180x69	180x69	22 - 23mm	24 - 25mm	26 - 27mm	28 - 29mm	30 - 31mm	32 - 33mm	34 - 35mm	36 - 37mm	38 - 39mm	40 - 41mm	42 - 43mm	44 - 45mm	46 - 47mm	48 - 49mm	50 - 51mm	52 - 53mm
67mm	energeto 5000 view Sash	-	→150x80	22 - 23mm	24 - 25mm	26 - 27mm	28 - 29mm	30 - 31mm	32 - 33mm	34 - 35mm	36 - 37mm	38 - 39mm	40 - 41mm	42 - 43mm	44 - 45mm	46 - 47mm	48 - 49mm	50 - 51mm	52 - 53mm
65mm	IDEAL 7000, IDEAL 8000, Nord-line ⁵⁾ frame, lift-slide ⁴⁾	→170x39	170x39	16 - 17mm	18 - 19mm	20 - 21mm	22 - 23mm	24 - 25mm	26 - 27mm	28 - 29mm	30 - 31mm	32 - 33mm	34 - 35mm	36 - 37mm	38 - 39mm	40 - 41mm	42 - 43mm	44 - 45mm	46 - 47mm
63mm	IDEAL 4000 + 8mm / IDEAL 5000 + 8mm / 180250 → 140x27, 140x48, 150x27	→140x27, 140x48, 150x27	140x27, 140x48, 150x27	12 - 13mm	14 - 15mm	16 - 17mm	18 - 19mm	20 - 21mm	22 - 23mm	24 - 25mm	26 - 27mm	28 - 29mm	30 - 31mm	32 - 33mm	34 - 35mm	36 - 37mm	38 - 39mm	40 - 41mm	42 - 43mm
55mm	IDEAL 4000, IDEAL 5000, Nord-line ⁵⁾ Sash, smart-slide ⁵⁾ 6)	→120x26, 120x82, 120x86, 140x46, 140x47	120x26, 120x82, 120x86, 140x46, 140x47	4 - 5mm	6 - 7mm	8 - 9mm	10 - 11mm	12 - 13mm	14 - 15mm	16 - 17mm	18 - 19mm	20 - 21mm	22 - 23mm	24 - 25mm	26 - 27mm	28 - 29mm	30 - 31mm	32 - 33mm	34 - 35mm
47mm	IDEAL 2000 → 120x220000096, 120x300000096, 120x310000096	→120x220000096, 120x300000096, 120x310000096	120x220000096, 120x300000096, 120x310000096	4mm	5mm	6mm	7mm	8mm	9mm	10mm	11mm	12mm	13mm	14mm	15mm	16mm	17mm	18mm	19mm
47mm	IDEAL 2000, multi-slide ⁵⁾	→120x220000096, 120x300000096, 120x310000096	120x220000096, 120x300000096, 120x310000096	4mm	5mm	6mm	7mm	8mm	9mm	10mm	11mm	12mm	13mm	14mm	15mm	16mm	17mm	18mm	19mm
38mm	vario-slide ⁵⁾	→120x220000096, 120x300000096, 120x310000096	120x220000096, 120x300000096, 120x310000096	4mm	5mm	6mm	7mm	8mm	9mm	10mm	11mm	12mm	13mm	14mm	15mm	16mm	17mm	18mm	19mm
32mm	easy-slide ⁵⁾	→120x220000096, 120x300000096, 120x310000096	120x220000096, 120x300000096, 120x310000096	4mm	5mm	6mm	7mm	8mm	9mm	10mm	11mm	12mm	13mm	14mm	15mm	16mm	17mm	18mm	19mm
20/22mm	mono-slide ⁵⁾ 6)	→120x220000096, 120x300000096, 120x310000096	120x220000096, 120x300000096, 120x310000096	4mm	5mm	6mm	7mm	8mm	9mm	10mm	11mm	12mm	13mm	14mm	15mm	16mm	17mm	18mm	19mm

b Glazing Beads		Glazing thickness																		
(CJ) Classic-line		10.5	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46
																				
h = 20mm 1) 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				
h = 30mm 2) back																				

Example for colour-coded part number

1. pos.	2. pos.	3. pos.	4. pos.	5. pos.	6. pos.	7. pos.	8. pos.	9. pos.
1	2	1	3	2	3	1	0	5
uPVC profiles	aluplast-systems: 0 = sliding / casement 4000 2 = IDEAL 2000 4 = IDEAL 4000	profile colour (carrier profile): 0 = white 1 = brown 2 = dark grey 3 = ocre 4 = regrind, coloured 9 = tropical	profile type: 0 = main profiles 1 = additional profile 2 = additional profile 3 = main profile with black gasket 4 = main profile with papyrus gasket 6 = glazing bead with 2-mm-gasket 7 = glazing bead with 6-mm-gasket 8 = glazing bead with 4-mm-gasket	profile sequence number		lamination type: 1 = inside and outside 2 = outside only	lamination colours: 27 = nut tree 23 = golden oak 89 = Black Brown 38 = Vermont Oak 79 = Alux DB 19 = turner oak malt (woodec) 22 = turner oak toffee (woodec) 03 = anthracite grey (aludec) 04 = jet black (aludec) aluplast natura aluplast farbwelt aluplast woodec / aludec	

→ Position 10-13 stands to the length of the profile in mm so "xxxxxxxxx5850" = 5.85 m